



INSULATING PLATFORMS (INDOOR MODELS)

Reference	Class	Rated insulation	Max work load kg	Standards	↑↓ (mm)	⚖️ (kg)
					Height	Weight
CT-7-25/1	4	≤ 36 kV	85	UNE 204 001	220	3.7
CT-7-40/1	4	≤ 45 kV	85	UNE 204 001	260	3.9

CT-701	4 pads set
--------	------------

BENEFITS

- Moulded insulating material, one-piece.
- Top 50 x 50 cm.



INSULATING PLATFORMS (INDOOR MODEL)

Adapted to High Voltage.

Reference	Rated insulation	Max work load kg	↑↓ (mm)	⚖️ (kg)
			Height	Weight
CT-7-63	≤ 63 kV	85	515	3.35

BENEFITS

- Removable feet with rubber pads.
- Moulded solid plate of insulating material 52 x 52 cm, thickness 40 mm.



INSULATING PLATFORM (OUTDOOR MODELS)

Reference	Rated insulation	Max work load kg	↑↓ (mm)	⚖️ (kg)
			Height	Weight
CT-9-25	≤ 24 kV	100	350	6
CT-9-45	≤ 45 kV	85	435	6.5
CT-9-63	≤ 63 kV	85	515	7

BENEFITS

- Moulded solid plate of insulating material 52 x 52 cm, thickness 40 mm.
- Insulating skirts.
- Feet with rubber pads.

